

ECOSORB® iAQ

Product Sheet

ECOSORB iAQ LIQUID/SPRAY FOR COMMERCIAL SPRAY APPLICATIONS

DESCRIPTION: Ecosorb iAQ Liquid/Spray is a broad spectrum, continuous release odor neutralizer:

- Contains no masking fragrances or harsh chemicals
- Is non-toxic and biodegradable
- Safe for use around people and pets
- Immediate acting, neutralizes malodors completely
- Naturally activated by air flow created by fine mist sprayer

APPLICATIONS: Commercial uses range from industrial and commercial processes, to food service operations, restrooms, nursing homes, hospitals and more. Ecosorb iAQ Liquid/Spray eliminates malodors created by or associated with:

- Animals & pets
- Body fluids
- Cooking
- Garbage
- Mold & mildew
- Tobacco or smoke damage
- Paint & household chemicals
- Rodents & pests

AVAILABILITY: Ecosorb iAQ Liquid/Spray comes in a variety of sizes to fit every commercial need.

DESCRIPTION	SOLD BY	CASE ITEM #
• 8 ounce spray bottle	Case pack / 12	Item No. 514
• 32 ounce spray bottle	Case pack / 12	Item No. 516
• 1 gallon refill jug	Case pack / 4	Item No. 510
• 5 gallon pail	Case pack / each	Item No. 511
• 55 gallon drum	Case pack / each	Item No. 512

ACTIVE INGREDIENTS: Filtered water, natural extracts of aniseed, cedarwood, clove, lime, and pine needle.

INTENTION: For commercial use only as directed. Keep out of reach of children. Do not leave pails or drums unattended. In case of eye contact, flush with water immediately. In case of ingestion, immediately drink several glasses of water. Use Ecosorb iAQ Liquid as follows:

- Ecosorb iAQ Liquid can be applied through a standard pressure or trigger sprayer to surfaces such as floors, walls, urinals, toilets and sinks for general odor control.
- Add 8 ounces of Ecosorb iAQ Liquid to 2 ½ gallons of mop water to destroy odors on hard floors such as tile and concrete as well as in floor drains.
- Ecosorb iAQ can be atomized into the air to control odors in a multitude of applications.
- Use full strength in trigger sprayers for immediate knockdown of odorous gases.
- Add Ecosorb iAQ to cool mist room humidifiers at a rate of 2 ounces per gallon of water. Dilution rates can be adjusted according to severity of odors.
- Fogging equipment: Use full strength at a rate of 1.5 oz / 1000 cubic feet of space. Highest rates of efficiency are achieved at 20 microns or lower.
- Carpet Cleaning: Mix at 2 ounces per gallon of water for use in extraction method carpet cleaning equipment and 4 ounces per gallon using bonnet method cleaning.

QUESTIONS: Contact us for sales, product capabilities information or for an MSDS.